END-OF-LINE



END HANDLING



ALF 130 AUTOMATIC LID FEEDER

Video

Introducing Fleetwood's ALF 130 Automatic Lid Feeders - a game-changer in lid handling. Say goodbye to the tedious and time-consuming process of manually unloading and feeding bagged lids. Our revolutionary technology takes care of it all, freeing up your valuable resources to focus on optimizing your filling operations. With the ALF 130, loading bags of lids becomes effortless as it effortlessly loads them with ease. But that's not all - our innovative feeder goes the extra mile by automatically removing each paper bag before seamlessly feeding the lids to the filling line. Take your lid handling to the next level with Fleetwood's ALF 130 Automatic Lid Feeders.



AMBEC | FLEETWOOD | GOLDCO | NIGRELLI | STACT | SWF



DESCRIPTION

Bagged sleeves of can lids are manually loaded onto the ALF's feed table to allow for continuous production with only periodic operator interaction. The feed table automatically indexes on-demand and supplies individual sleeves to the ALF. One-by-one, sleeves are automatically fed in and oriented to an optimum cutting position. In a smooth continuous motion, each bag is cleanly slit along the full length of the bag without touching the lids. The bags are then completely removed and gravity dropped down into a scrap bin under the machine.

The ALF 130 provides a constant, reliable flow of lids to the filling line and is a cost-effective solution for beverage or food processors using single infeed can seamers. All Fleetwood equipment is designed around the same customer-focused, reliable, and innovative approach that has made us a leader in the can end market since 1956.

FEATURES

- Small footprint
- Easy loading and delivers product on demand
- Low maintenance requirements
- Reliable 24/7 operation
- Automatic reversed end detection and ejection system
- Designed for easy operator and maintenance access
- Change parts available for product size changes
- User-friendly Allen-Bradley PLC controls

AVAILABLE OPTIONS

- Custom conveyor solutions and layouts
- Stainless-steel construction
- Slinky packages for priming and purging lids from Siemens PLC control system trackwork



- Various bag feed table capacities
- Product size change parts

Speed	Product Sizes	Packaged Sleeve Length (Min/Max)	Scrap Bag Capacity
• Up to 3 bags per minute (90,000 cph)	From 200 to 209 diameter	• 36" - 48" (915 mm - 1200 mm) with change parts	• Up to 400

Contact our experienced sales teams today for a comprehensive review of your application(s) and to see how our Automatic Lid Feeders can benefit your company.

