



HARLAND
by **bw** packaging

LABELING

PRESSURE SENSITIVE



SIRIUS MK6

Introducing the Sirius MK6 labeling system. With over 50 years of industry experience, the Sirius MK6 is a highly versatile and adaptable labeling solution that has been engineered to meet the ever-changing needs of modern-day labeling. Whether you need to label simple or more complex container shapes, the Sirius MK6 provides the right solution for you. Its robust and modular design allows for efficient configuration based on your current production or financial needs, with the option for future upgrades if your requirements change. At Harland, we aim to provide you with more than just labeling solutions. We empower your business to thrive by ensuring seamless repeatability, minimal downtime, and reduced waste.

Harland Sirius MK6 Pressure Sensitive Labeler

FEATURES

- Fully synchronized servo-driven axis
- Toolless changeovers
- Digital position indicators
- User-friendly next-generation smart HMI interface

AVAILABLE OPTIONS

- PackML
- Safety PLC's
- Industry 4.0
- Pharmaceutical: 21 CFR part 11 & validation packages
- Siemens or Allen-Bradley/Rockwell controls
- Label overprint by TTO, CIJ, laser or hot foil
- Vision inspection system - sensor, scanner or camera
- Fail safe, track-and-reject systems with verification
- Queue control
- Fallen bottle detection

- Rugged robust design
- Reliable 24 / 7 operation
- Designed for easy operator and maintenance access
- Global certification – UKCA, CE, UL, (others available)

- Front, back, top & wrap labeling options
- Infeed & outfeed container transfer via side belts, conveyor flush sides
- Product pitching via servo scroll, gapping wheel or gapping unit
- Product orientation via chain aligners, centering units, or tri-roller
- Label wipe down via heavy-duty wipes, foam rollers, or walking beam module for complex container and label profiles



Sirius MK6



Product Feed Screws

Production Rates	Product Capacity	Label Capacity	Services	Standard Footprint
<ul style="list-style-type: none">• Linear up to 300ppm• 3-roller wrap up to 60ppm	<ul style="list-style-type: none">• Max Height: 13.78" (350mm)• Min Height: 0.78" (20mm)• Max Width: 7.87" (200mm)• Min Width: 0.59" (15mm)	<ul style="list-style-type: none">• Max Web Width: 12" (305mm)• Min Web Width: 0.39" (10mm)	<ul style="list-style-type: none">• 220-240Vac 20A 1Ph + E, 50/60 Hz• Air may be required for some printers and security options	<ul style="list-style-type: none">• Length: 118.11" (3000mm)• Width: 118.11" (1300mm) - 1 head one side• Width: 82.67" (2100mm) - 1 head both sides• Height: 78.74" (2000mm)

All specification and tooling requirements are subject to evaluation of all label and product samples.
Specifications shown reflect standard machine capabilities. Integration of additional features may vary the data.
Customization to meet other specifications available, please contact for further details.

Contact our experienced sales teams today for a comprehensive review of your application(s) and to see how our Sirius MK6 Labelers can benefit your company.