



Video 🌓

CASE ERECTING



SWF CE 450 Case Erectors - robust, high-speed machines that effortlessly fold and seal the bottom flaps of RSC or HSC cases using hot-melt adhesive. Our standard machine is capable of running up to 30 cases per minute, employing cost-effective air cylinder operation. For even greater speeds, above 30 cases per minute, we offer the option to utilize servo motors. The CE 450 is ingeniously designed around mechanical simplicity, employing opposed vacuum opening and positive case transfer techniques.

Video






Video

DESCRIPTION

For over six decades, SWF has been at the forefront of providing top-quality packaging equipment solutions for various industries. Their bliss, tray, and case erecting product line has consistently been a leader in the industry, and they have helped countless businesses determine the best packaging design and machinery solution for their application. Their equipment boasts several features that make it an ideal choice for businesses of all sizes, including a small footprint, rugged 24/7 construction, simple operator interface, and quick changeover time. Additionally, the equipment comes equipped with a pressurized hot-melt glue system, an automatic jam shutdown sensor, and polycarbonate interlocked guards and doors for added safety. With thousands of installations worldwide and backed by a world-class service team, you can trust SWF to provide you with the highest quality packaging equipment for your business.

AVAILABLE OPTIONS

- High capacity powered hoppers
- 6' hopper capacity: 270 C-flute
- 11' hopper capacity: 390 C-flute
- 15' hopper capacity: 540 C-flute
- Corrosion resistant packages
- Servo actuation for higher speeds
- Discharge conveyors



| Speed | Case Size Capabilities | Knocked Down |
|---|--|--|
| Up to 40 cases per minute (dependent on size and style) | Length: 8" - 20" (20.32 cm - 50.80 cm) Width: 5" - 14" (12.7 cm - 35.60 cm) Depth: 5" - 14" (12.7 cm - 35.60 cm) | A Dimension: 13" - 34" (33.02 cm - 86.40 cm) B Dimension: 11" - 24" (27.90 cm - 61.00 cm) S (Depth+Top+Flaps): 8" - 19" (20.30 cm - 48.30 cm) C (Flaps to be glued): 3" - 6" (7.60 cm - 15.20 cm) |
| Note: Specifications subject to change without notice | | |

Contact our experienced sales teams today for a comprehensive review of your application(s) and to see how our Case Erectors can benefit your company.

