

C-1250 Friction Feeder

Overview

Streamfeeder's C-1250 is designed for dependable one-shot and batch count feeding for packaging operations pursuing greater productivity through automation. Tool-less, make ready adjustments and versatility provides increased uptime, maximizing return on investment.

Feed a wide variety of flat and multi-thickness products into shrink wrappers, poly baggers, banders, collators, case packers, boxes, and more. Operates on-demand one at a time or in batch sets up to 99 pieces.

Standard Features

- rubber feed belts
- Miss-detect
- Photo-sensor trigger
 Two-knob side guide
- Long lasting natural
 Stainless steel construction
 - Timeout stop
 - Trigger delay
 - positioning

Optional Features

- Adjustable discharge Extended vacuum
- Double sheet detect
- Low stack detect
- transport
- Tower lamp

Applications

- Cartoners
- Case Packers
- Collators
- Envelope Inserters
- Flow Wrappers
- Order Fulfillment
- Poly Baggers
- Shrink Wrappers

Products

- Backer Board
- Booklets
- Brochures
- Cardstock
- Collapsed Cartons
- Envelopes
- Folded Documents
- Folders
- Literature
- Manuals
- Retail Signage
- Sheet Paper

Contact our experienced sales team today for a comprehensive review of your application/product and see how our C-1250 can benefit your company.



Specifications

Maximum Product Size

12" wide x 14" long (305 x 357 mm)

Minimum Product Size

2" wide x 2.5" long (51 x 64 mm)

Min/Max Product Thickness

.003" to 1.0" (.076 to 25.4 mm)

Belt Speed

4,000 in/min (101.6 m/min)

Batch Size

1-99

Litilities

115/230vac, 50/60 Hz, 12/6A (configured)

Feeder: 50 lbs. (23 kg); Control Box: 36 lbs. (16.3 kg)

Warranty

One year limited

Other sizes and thickness capabilities available.

AMBEC | CBI | Fleetwood | Goldco | Nigrelli | Streamfeeder | SWF | Thiele | Tisma Streamfeeder - BW Integrated Systems

