

Flex Feeder

Overview

Streamfeeder's Flex Feeder dispenses difficult to feed products that may be flexible, thin or flimsy, uneven or are not uniform in shape. Our Flex Feeder solves this challenge by efficiently shingling the product while supporting the entire piece through the feeder.

The Flex Feeder is ideal for operations in food and consumer goods packaging by automating product dispensing in applications including coding, labeling, ink jet printing, scanning, verification and more. A vacuum transport and optional shingling conveyor can be added to offer a complete system solution.

Standard Features

- Adjustable feed belts
- Casters, leveling feet
- Push button controls
- Variable speed control
- Dual feed belts with soft and hard separator plates
- Product alignment guides

Optional Features

- System integration with downstream machines

Applications

- Addressing
- Attaching
- Coding
- Date stamping
- Labeling
- Printing
- Scanning
- Tabbng
- Tip-On/Affixing
- Verification

Products

- Paper bags
- Plastic bags
- Foil pouches
- Valve pouches
- Zip lock bags
- and more

Contact our experienced sales team today for a comprehensive review of your application/product and see how our Flex Feeder can benefit your company.



Specifications

Maximum Product Size	19.5" wide x 28" long (495 x 711 mm)
Minimum Product Size	3" wide x 4" long (76.2 x 101.6 mm)
Maximum Product Thickness (Standard Configuration)	.75 in (19.05 mm)
Utilities	110vac, 1 Phase, 10A
Dimensions	53" long x 28.5" wide x 33-36" high (135 x 72.4 x 84-91 cm)
Warranty	One year limited
Higher speeds and other sizes/thickness capabilities available.	

AMBEC | Fleetwood | Goldco | Nigrelli | Streamfeeder | SWF | Tisma

